

SERCO REKO TVH ROLLER FRAME SPREADER

Towable crushing spreader!

- Reko TVH Roller Frame Spreaders are available in four sizes
- Hydraulically operated, manually adjustable rotation speed
 - The spreading capacity is adjusted from the flow control valve on the side of the machine, or if the oil flow of the base machine can be adjusted, the capacity can also be adjusted from the cab
- Hydraulic requirements: 1 hose pair for the roller and 1 hose pair the hydraulically operated bottom hatch
 - Oil flow max.: 100 l/min
- Standard equipment:
 - Standard equipment:
 - Crusher rotor
 - Support leg
 - Hydraulic brakes
 - Screen/grille
 - Hydraulically operated bottom hatch
 - Tarpaulin
 - Truck tyres
 - Hydraulic quick couplers of your choice

Spreading of sand, crushed gravel and salt.



MODEL	Product number	Capacity	Weight	Width	Working width	Height	Length	Tyre size
Reko 1500TVH	606146	1500 L	1260 kg	2200 mm	2000 mm	1280 mm	3520 mm	285/70R19.5
Reko 3000TVH	605572	3000 L	1520 kg	2200 mm	2000 mm	1820 mm	3520 mm	285/70R19.5
Reko 5000TVH	605573	5000 L	2100 kg	2370 mm	2200 mm	2020 mm	4100 mm	295/60R22.5
Reko 8000TVH	605574	8000 L	2700 kg	2760 mm	2600 mm	2100 mm	4540 mm	385/65R22.5